

Three Pole Definite Purpose Contactor

Product

EC303 Series Contactors

Purpose

The DiversiTech Definite Purpose contactors can be used for heating, air conditioning, refrigeration, data processing, and food service equipment. Quick connect terminals provide for easy wiring. This contactor comes as a three pole on a large frame.

Features

- Cost effective
- Easy to install
- UL Recognized

General Specifications

- UL Recognized
- 3 Pole
- Coil Voltage Available:
 - o 120 VAC
 - o 24 VAC
 - o 240 VAC
 - o 277 VAC
- Foot Mounting
- 1 year warranty

General Characteristics

Catalog Number	Coil VA	Amps	Dimensions	Weight
EC303120	120	30	H = 3.25, W = 3.0, D = 4.0	1 LBS
EC30324	24	30	H = 2.5, W = 3.25, D = 4.5	1 LBS
EC303240	240	30	H = 2.5, W = 3.25, D = 4.25	1.06 LBS
EC303277	277	30	H = 4.53, W = 2.66, D = 3.1	1 LBS
EC403120	120	40	H = 3.25, W = 2.75, D = 4.25	1 LBS
EC40324	24	40	H = 3.25, W = 4.25, D = 2.75	1.02 LBS
EC403240	240	40	H = 2.63, W = 3.25, D = 4.13	1.06 LBS
EC403277	277	40	H = 4.53, W = 2.66, D = 3.11	1 LBS
EC503120	120	50	H = 2.66, W = 3.11, D = 4.5	1.1 LBS
EC50324	24	50	H = 2.66, W = 3.11, D = 4.53	1.1 LBS
EC503240	240	50	H = 2.66, W = 3.11, D = 4.53	1.1 LBS
EC503277	277	50	H = 4.53, W = 2.66, D = 3.11	1.1 LBS
EC603120	120	60	H = 2.66, W = 3.11, D = 4.53	1.1 LBS
EC60324	24	60	H = 2.66, W = 3.11, D = 4.53	1.1 LBS
EC603240	240	60	H = 2.66, W = 3.11, D = 4.53	1.1 LBS
EC603277	277	60	H = 4.53, W = 2.66, D = 3.11	1.1 LBS
EC753120	120	75	H = 3.5, W = 4.53, D = 5.24	3.3 LBS
EC75324	24	75	H = 3.5, W = 4.53, D = 5.24	3.3 LBS
EC753240	240	75	H = 3.5, W = 4.53, D = 5.24	3.3 LBS
EC753277	277	75	H = 5.24, W = 3.5, D = 4.53	3.3 LBS
EC903120	120	90	H = 3.5, W = 4.53, D = 5.24	3.3 LBS
EC90324	24	90	H = 3.5, W = 4.53, D = 5.24	3.3 LBS
EC903240	240	90	H = 3.5, W = 4.53, D = 5.24	3.3 LBS
EC903277	240	90	H = 5.24, W = 3.5, D = 4.53	3.3 LBS

