

## CPVC-CTS Fittings

### Product

CPVC-CTS Fittings by FlowGuard® Gold™

### Application

Plumbing

### Purpose

Flowguard® Gold™ is a patented CPVC formulated compound developed by BF Goodrich to improve the impact resistance of CPVC hot and cold water plumbing products.

### Maximum Temperature

Maximum temperature 180°F

### Type

Schedule 40

### Dimensions

- 4701-34: D = 1.5", W = 1.0", H = 1.0"
- 4703-34: D = 2.75", W = 2.75", H = 2.25"
- 4704-12: D = 1.5", W = 0.5", H = 0.5"
- 4704-34: D = 1.75", W = 1.25", H = 1.25"
- 4706-34: D = 2.0", W = 1.0", H = 2.0"
- 4707-12: D = 1.75", W = 1.0", H = 1.75"
- 4707-34: D = 1.75", W = 1.0", H = 1.75"
- 47072-12: D = 1.75", W = 1.0", H = 1.75"
- 47072-34: D = 2.0", W = 1.25", H = 2.0"
- 4711-12: D = 2.5", W = 1.0", H = 1.5"
- 4711-34: D = 2.25", W = 1.0", H = 0.2"
- 4718-12: D = 0.88", W = 0.88", H = 0.75"



4701-34



4703-34



4704-12, 4704-34



4706-34



4707-12, 4707-34



47072-12, 47072-34



4711-12, 4711-34



4718-12

## SKU Specific Package Metrics

Cat. No.	Dimensions	Max. Temp.	Max. Pressure	UPC	Order Multiple
<b>4701-34</b>	3/4 in. Coupling S x S	180°F	480 PSI	0095247071944	20
<b>4703-34</b>	3/4 in. Adapter F x S	180°F	480 PSI	0025528136901	25
<b>4704-12</b>	1/2 in. Adapter M x S	180°F	590 PSI	0039923299291	20
<b>4704-34</b>	3/4 in. Adapter M x S	180°F	480 PSI	0039912107262	10
<b>4706-34</b>	3/4 in. 45 degree Elbow S x S	180°F	480 PSI	0095247071968	20
<b>4707-12</b>	1/2 in. 90 degree Elbow S x S	180°F	590 PSI	0039912107682	20
<b>4707-34</b>	3/4 in. 90 degree Elbow S x S	180°F	480 PSI	0039923107701	20
<b>47072-12</b>	1/2 in. 90 degree Street Ell S x S	180°F	590 PSI	0095247071975	10
<b>47072-34</b>	3/4 in. 90 degree Street Ell S x S	180°F	480 PSI	0039912107781	10
<b>4711-12</b>	1/2 in. Tee S x S x S	180°F	590 PSI	0095247071982	20
<b>4711-34</b>	3/4 in. Tee S x S x S	180°F	480 PSI	0039923107848	20
<b>4718-12</b>	3/4 in. x 1/2 in. CPVC Bushing	180°F	590 PSI	0095247071999	10